

WHAT IS CLAIMED IS:

1. A method for communicating data, comprising:
communicating a first set of data from a first
channel to a first serial-to-parallel converter and
5 communicating a second set of data from a second channel
to a second serial-to-parallel converter;
converting the first and seconds sets of data to a
parallel format;
monitoring the first and second serial-to-parallel
10 converters in order to determine when one or more words
of the respective data sets have accumulated in each of
the first and second serial-to-parallel converters;
writing one or more of the words that have
accumulated in each of the first and second serial-to-
15 parallel converters to a selected one of first and second
memory banks;
monitoring, by a single scheduler, the first and
second memory banks to determine when enough of the words
that were written to each of the first and second memory
20 banks have formed one or more cells; and
reading one or more of the cells out of a selected
one of the first and second memory banks such that they
may be communicated to an output communications link.

25 2. The method of Claim 1, further comprising
generating a memory address for each of the one or more
words to be written into the first and second memory
banks, the memory addresses designating the space where
the one or more words are written to in the first and
30 second memory banks.

3. The method of Claim 2, further comprising receiving one or more of the cells that are read out of the first and second memory banks at an ATM switch.

5 4. The method of Claim 1, wherein the reading of the cells out of the first and second memory banks is executed by a scheduler that is coupled to the first and second memory banks and a Utopia bus.

10 5. The method of Claim 1, further comprising providing a select controller, which is coupled to the first and second serial-to-parallel converters, the select controller being operable to determine which of the first and second memory banks the words, which have
15 accumulated in each of the first and second serial-to-parallel converters, are written to.

20 6. The method of Claim 5, further comprising communicating a write enable signal from the select controller to a selected one of the first and second memory banks to indicate that one or more of the words, which have accumulated in each of the first and second serial-to-parallel converters, is ready to be written.

25 7. The method of Claim 6, further comprising signaling, by the select controller, to a multiplexer to communicate one or more of the words, which have accumulated in each of the first and second serial-to-parallel converters, to a selected one of the first and
30 second memory banks.

Year	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100
1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	

9. An apparatus for communicating data, comprising:

5 a multiplexer operable to receive one or more words associated with a respective one of a first and a second set of data, wherein the first and second sets of data are associated with a first channel and a second channel respectively;

10 first and second memory banks each coupled to the multiplexer and each operable to receive one or more of the words from the multiplexer; and

15 a scheduler coupled to each of the first and second memory banks and operable to read one or more cells out of a selected one of the first and second memory banks, wherein each of the cells comprises a plurality of the words from a respective one of the first and second sets of data.

20 10. The apparatus of Claim 9, further comprising a first write controller associated with the first channel and a second write controller associated with a second channel, wherein the first and second write controllers are each operable to communicate one or more of the words to the multiplexer.

25 11. The apparatus of Claim 10, further comprising a select controller coupled to the multiplexer and operable to determine which of the first and second memory banks the words are written to.

12. The apparatus of Claim 11, further comprising first and second serial-to-parallel converters, the first serial-to-parallel converter coupled to the first write controller and operable to convert the first set of data to a parallel form before the first set of data is received by the first write controller, the second serial-to-parallel converter coupled to the second write controller and operable to convert the second set of data to a parallel form before the second set of data is received by the second write controller.

13. The apparatus of Claim 9, further comprising a Utopia bus coupled to the scheduler and operable to communicate one or more of the words from the scheduler to an asynchronous transfer mode (ATM) switch.

14. The apparatus of Claim 13, further comprising a demultiplexer coupled to the ATM switch and the Utopia bus and operable to provide a communications interface therebetween.

15. The apparatus of Claim 9, further comprising a dual-port memory coupled to the multiplexer and the scheduler, wherein the first and second memory banks are included within the dual port memory.

16. A system for communicating data, comprising:
means for communicating a first set of data from a
first channel to a first serial-to-parallel converter and
communicating a second set of data from a second channel
5 to a second serial-to-parallel converter;
means for converting the first and seconds sets of
data to a parallel format;
means for monitoring the first and second serial-to-
parallel converters in order to determine when one or
10 more words of the respective data sets have accumulated
in each of the first and second serial-to-parallel
converters;
means for writing one or more of the words that have
accumulated in each of the first and second serial-to-
15 parallel converters to a selected one of first and second
memory banks;
means for monitoring, by a single scheduler, the
first and second memory banks to determine when enough
words have accumulated in the first and second memory
20 banks to form one or more cells; and
means for reading one or more of the cells out of
the first and second memory banks such that they may be
communicated to an output communications link.

25 17. The system of Claim 16, further comprising
means for generating a memory address for each of the one
or more words to be written into the first and second
memory banks, the memory addresses designating the space
where the one or more words are written to in the first
30 and second memory banks.

18. The system of Claim 17, further comprising means for receiving one or more of the cells that are read out of the first and second memory banks at an ATM switch.

5

19. The system of Claim 18, wherein the reading of the cells out of the first and second memory banks is executed by a scheduler that is coupled to the first and second memory banks and a Utopia bus.

10

20. The system of Claim 16, further comprising means for determining which of the first and second memory banks the words, which have accumulated in each of the first and second serial-to-parallel converters, are written to.

15

21. The system of Claim 20, further comprising means for communicating a write enable signal to a selected one of the first and second memory banks to indicate that one or more of the words, which have accumulated in each of the first and second serial-to-parallel converters, is ready to be written.

20

22. The system of Claim 21, further comprising means for signaling to a multiplexer to communicate one or more of the words, which have accumulated in each of the first and second serial-to-parallel converters, to a selected one of the first and second memory banks.

25

24. Software for communicating data embodied in a computer readable medium and operable to:

communicate a first set of data from a first channel to a first serial-to-parallel converter and communicating
5 a second set of data from a second channel to a second serial-to-parallel converter;

convert the first and seconds sets of data to a parallel format;

monitor the first and second serial-to-parallel
10 converters in order to determine when one or more words of the respective data sets have accumulated in each of the first and second serial-to-parallel converters;

write one or more of the words that have accumulated in each of the first and second serial-to-parallel
15 converters to a selected one of first and second memory banks;

monitor, by a single scheduler, the first and second memory banks to determine when enough words have accumulated in the first and second memory banks to form
20 one or more cells; and

read one or more of the cells out of the first and second memory banks such that they may be communicated to an output communications link.

25 25. The software of Claim 24, further operable to generate a memory address for each of the one or more words to be written into the first and second memory banks, the memory addresses designating the space where the one or more words are written to in the first and
30 second memory banks.

26. The software of Claim 25, further operable to receive one or more of the cells that are read out of the first and second memory banks at an ATM switch.

5 27. The software of Claim 26, wherein the reading of the cells out of the first and second memory banks is executed by a scheduler that is coupled to the first and second memory banks and a Utopia bus.

10 28. The software of Claim 24, further operable to determine which of the first and second memory banks the words, which have accumulated in each of the first and second serial-to-parallel converters, are written to.

15 29. The software of Claim 24, further operable to communicate a write enable signal to a selected one of the first and second memory banks to indicate that one or more of the words, which have accumulated in each of the first and second serial-to-parallel converters, is ready
20 to be written.

30. The software of Claim 24, further operable to signal to a multiplexer to communicate one or more of the words, which have accumulated in each of the first and
25 second serial-to-parallel converters, to a selected one of the first and second memory banks.

31. The software of Claim 24, further operable to increment an address associated with a selected one of the first and second memory banks each time one of the words, which have accumulated in each of the first and
5 second serial-to-parallel converters, is written to one of the first and second memory banks.

11/11/2011 10:00 AM

32. An apparatus for communicating data, comprising:

5 a multiplexer operable to receive first and second sets of data, wherein the first and second sets of data are associated with a first channel and a second channel respectively;

a first write controller associated with the first channel and a second write controller associated with the second channel;

10 first and second serial-to-parallel converters, the first serial-to-parallel converter coupled to the first write controller and operable to convert the first set of data to a parallel form before the first set of data is received by the first write controller, the second
15 serial-to-parallel converter coupled to the second write controller and operable to convert the second set of data to a parallel form before the second set of data is received by the second write controller;

20 first and second memory banks each coupled to the multiplexer and each operable to receive from the multiplexer one or more words that have accumulated in each of the serial-to-parallel converters and that comprise a portion of a selected one of the first and second sets of data;

25 a scheduler coupled to each of the first and second memory banks and operable to read a cell out of a selected one of the first and second memory banks, wherein the cell comprises a plurality of the words; and

30 a select controller coupled to the multiplexer and operable to determine which of the first and second memory banks the words are written to.